



R25 Rotator

The R25 rotator features a RS-485 computer control to remotely orient equipment. It also features a 3,000 depth rating, 45 lb-ft torque, 24-30 VDC power, aluminum housing, and oil or air filled models. The R25 has a 1-year warranty and various connector options

Payload	100 lbs (45 kg)
Torque	45 lb/ft (61 N-m)
Accuracy	+/- 1.5° (90 arc minutes)
Gear Backlash	0.5° (30 arc minutes)
Scan Range	+/- 360 degrees max
Rotation Speed	0.5 - 10° / sec
Power	24-30 VDC (1.7 amps)
Control	RS-485 (half duplex)
Networkability	up to 32 RS-485 nodes
Motors	Brushless stepper
Depth rating	oil filled: 3,000 meters, air filled: 30 meters
Housing material	aluminum
Size	4.90 "H x 4.2"D (124 mm x 107 mm)
Weight	in air 10.5 lb (air), 11.7 lb (oil); water: 6.5 lb (air), 7.7 lb (oil)
Operating temp	up to 122° F (50° C); storage temp: -4° to 140° F (-20 to 60°C)
Connectors	Impulse LPMBH-4-MP



5618 Copley Drive, San Diego, CA 92111
858.565.8500 | www.rosys.com | sales@rosys.com